PCT





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 7:

A1

(11) International Publication Number:

WO 00/54831

A61M 25/06, 5/32

(43) International Publication Date:

21 September 2000 (21.09.00)

(21) International Application Number:

PCT/IB00/00287

(22) International Filing Date:

17 March 2000 (17.03.00)

(30) Priority Data:

99/2146

17 March 1999 (17.03.99)

ZA

(71)(72) Applicants and Inventors: DUGMORE, Peter, Balfour [ZA/ZA]; 4 Swanmore Road, Rondebosch, 7700 Cape Town (ZA). BULL, Anthony, Eric [ZA/ZA]; 31 Grotto Road, Rondebosch, 7700 Cape Town (ZA). REYNOLDS, Stanford, William, Gladwin [ZA/ZA]; 18 Hopson Road, 3630 Westville (ZA).


(74) Agents: GILSON, David, Grant et al.; Spoor and Fisher, Rochester Place, 173 Rivonia Road, Morningside, Sandton, P.O. Box 41312, 2024 Craighall (ZA).

(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published

With international search report.

(54) Title: A SAFETY ASSEMBLY FOR A HYPODERMIC APPLICATOR SET



(57) Abstract

A cannula safety assembly (82) includes a cannula safety shield (84) and an elongate retractor (86). The retractor (86) is provided with a central plunger (98) which extends through a rear open end (85) of the safety shield and a pair of caliper arms (102) which fit over the safety shield. A needle assembly (88) includes a needle seat (108) from which a hollow needle (106) extends so that the needle assembly (88) is mounted detachably to the front end of the plunger (98), and the needle shield (96) is fitted over the front end of the safety shield, and mounted detachably to the ends of the caliper arms (102). The needle assembly (88) is slidably moveable in concert with the retractor (86) from an extended administrable position to a retracted position in which the needle (106) is fully withdrawn into the safety shield chamber by the retractor to be held safely captive within the chamber. The retractor is separable from the needle seat when in the retracted position. The invention extends to a method of manufacturing a cannula safety assembly.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
ΑT	Austria	FR	France	LU	Luxembourg	SN	Senegal
ΑU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
ΑZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	ΙL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Vict Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
СМ	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		
			•				